

DATASHEET

FUJITSU PRIMERGY TX300 S6 SERVER

NO COMPROMISE TOWER SERVER

PRIMERGY TX industry standard tower servers: efficient, rock solid, record-breaking performance. PRIMERGY TX servers benefit from over 20 years pioneering work in the field of Green IT. That is how TX servers reach industry – leading performance per watt ratios, lowering the environmental impact and running costs. TX servers can easily be managed via the free of charge PRIMERGY ServerView Suite, saving IT admin costs. That's efficient performance. Our made-to-measure service packages take care of your system every step of the way. Rest assured, PRIMERGY TX servers are put through 5000 boot cycles - that's rock solid performance. PRIMERGY TX servers are flexible systems capable of using up to two processors and up to 20 hard disks. Tower to rack mounting kits are available for most TX systems to help you move to a consolidated rack infrastructure. TX servers have a tradition of setting record-breaking performance levels. So, whether you use them as tower or rack servers, for file, print or application purposes, you will benefit from record-breaking performance. PRIMERGY TX: a tower of strength.

PRIMERGY TX300 S6

Are you looking for business continuity, especially for your core business applications? The new TX300 S6 offers maximum levels of availability and expandability as a result of hot plug, redundant versions. It has powerful performance features as supplied by the leading Intel® Xeon® processors 5600 series together with an 8-port SAS 2.0 controller and fast PCIe Gen2 connections. Continuity is ensured as a result of the modular RAID, redundant Dual LAN features and optional redundant hot-plug power supply and fans. The "Cool-safe™" technology in the new honeycomb design ensures optimal temperatures despite peak workloads and thus ensures long-life. Optimal performance and high energy efficiency is achieved via a highly efficient power supply (92% energy efficiency), a largely no-cable motherboard and state of the art power management features. The PRIMERGY TX300 S6 has 18 DIMM slots for memory mirroring with up to 192 GB DDR3 RAM. The PRIMERGY TX300 S6 is exactly the right platform for business-critical remote sites.



FEATURES AND BENEFITS

MAIN FEATURES	BENEFITS
<ul style="list-style-type: none"> ■ Intel® Xeon® Processor 5600 Series with up to 6 core operation (up to 12 threads per socket with Hyper Threading), 12 MB shared cache, Internal Memory Management Unit (3 channels of DDR3 memory) and Intel® Turbo Boost Optimization ■ More and faster memory (18 DIMMs up to 192 GB DDR3) ■ Hot-plug, redundant power supply and fan option, hot-plug SAS 2.0 or SATA hard disks, modular RAID 5/6 option, Dual Gbit/s LAN, Local Service Panel (LSP) or Local Service display (LSD) module ■ Internal max. 6 (8 optional)x SAS or SATA 3.5" HDD or up to 12 (20 optional)x SAS or SATA 2.5" HDD, all hot-plug, 7 PCIe Gen2 slots (2 x8, 5 x4) ■ Unique, patented solution for maximum I/O bandwidth with 7x PCIe Gen2 x8 slots (two x4 wired slots are automatically used as one x8 if the neighbouring slot is empty) 	<ul style="list-style-type: none"> ■ Higher overall productivity thanks to excellent CPU performance. ■ Innovative memory for system reliability, with maximum memory protection mechanisms, ideal for virtualization. ■ Highest availability and redundancy for your core applications. ■ Highest flexibility on account of state-of-the-art I/O technologies to consolidate data and applications. ■ Maximum possible I/O bandwidth; no expensive card in an empty slot required!

TECHNICAL DETAILS

MAINBOARD

Mainboard type	D 2619
Chipset	Intel® 5520
Processor quantity and type	1 - 2 x Intel® Xeon® processor 5600 series

PROCESSOR

Intel® Xeon® processor E5503 (2C/2T, 2.00 GHz, SLC: 4 x 256 KB, TLC: 4 MB, Turbo: No, 4.8 GT/s, Mem bus: 800 MHz, 80 W)
Intel® Xeon® processor E5506 (4C/4T, 2.13 GHz, SLC: 4 x 256 KB, TLC: 4 MB, Turbo: No, 4.8 GT/s, Mem bus: 800 MHz, 80 W)
Intel® Xeon® processor E5507 (4C/4T, 2.26 GHz, SLC: 4 x 256 KB, TLC: 4 MB, Turbo: No, 4.8 GT/s, Mem bus: 800 MHz, 80 W)
Intel® Xeon® processor E5620 (4C/8T, 2.40 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 80 W)
Intel® Xeon® processor E5630 (4C/8T, 2.53 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 80 W)
Intel® Xeon® processor E5640 (4C/8T, 2.66 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 80 W)
Intel® Xeon® processor L5609 (4C/4T, 1.86 GHz, SLC: 4 x 256 KB, TLC: 4 MB, Turbo: No, 4.8 GT/s, Mem bus: 800 MHz, 40 W)
Intel® Xeon® processor L5630 (4C/8T, 2.13 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 5.86 GT/s, Mem bus: 1066 MHz, 40 W)
Intel® Xeon® processor L5640 (6C/12T, 2.26 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/3/3/4/4, 6.4 GT/s, Mem bus: 1333 MHz, 60 W)
Intel® Xeon® processor X5650 (6C/12T, 2.66 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)
Intel® Xeon® processor X5660 (6C/12T, 2.80 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)
Intel® Xeon® processor X5667 (4C/8T, 3.06 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)
Intel® Xeon® processor X5670 (6C/12T, 2.93 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 2/2/2/2/3/3, 6.4 GT/s, Mem bus: 1333 MHz, 95 W)
Intel® Xeon® processor X5677 (4C/8T, 3.46 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/2/2, 6.4 GT/s, Mem bus: 1333 MHz, 130 W)
Intel® Xeon® processor X5680 (6C/12T, 3.33 GHz, SLC: 4 x 256 KB, TLC: 12 MB, Turbo: 1/1/1/1/2/2, 6.4 GT/s, Mem bus: 1333 MHz, 130 W)

Memory slots	18 (9 DIMMs per CPU, 3 channels with 3 slots per channel)
Memory slot type	DIMM (DDR3) registered
Memory capacity (min. - max.)	2 GB - 192 GB
Memory protection	Advanced ECC Memory Scrubbing SDDC (Chipkill™) Hot-spare memory support Memory Mirroring support

Memory notes	max. 192 GB registered,; min. 2 GB registered; Memory Mirroring with 2 identical modules, Hot-spare Memory with three identical modules per channel
---------------------	--

MEMORY MODULES INDEPENDENT MODE

2 GB (1 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
2 GB (1 module(s) 2 GB) DDR3, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM
2 GB (1 module(s) 2 GB) DDR3 LV, unbuffered, ECC, 1333 MHz, PC3-10600, DIMM
4 GB (1 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
4 GB (1 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
8 GB (1 module(s) 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
16 GB (1 module(s) 16 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM

MEMORY MODULES MIRRORED MODE	4 GB (2 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	8 GB (2 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	8 GB (2 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	16 GB (2 module(s) 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	16 GB (2 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	32 GB (2 module(s) 16 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM

MEMORY MODULES SPARE OR PERFORMANCE MODE	6 GB (3 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	12 GB (3 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	12 GB (3 module(s) 4 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	24 GB (3 module(s) 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600, DIMM
	24 GB (3 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM
	48 GB (3 module(s) 16 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500, DIMM

INTERFACES

USB ports	10 x USB 2.0 (3x front, 4x rear, 2x internal for backup devices plus 1x USB stick)
Graphics (15-pin)	2 x VGA (thereof 1x front optional)
Serial 1 (9-pin)	1 x serial RS-232-C, usable for iRMC S2 or system or shared
Serial 2 (9-pin)	1 x serial RS-232-C
LAN / Ethernet (RJ-45)	2 x Gbit/s Ethernet
Service LAN (RJ45)	1 x dedicated service LAN port for iRMC S2 (10/100 Mbit/s) Service LAN traffic can be switched to shared onboard Gbit LAN port

ONBOARD OR INTEGRATED CONTROLLER

RAID Controller	Integrated RAID 0/1 or RAID 5/6 controller for SAS base units (option, occupies one PCIe slot). See under Components RAID controller
SATA Controller	ICH10B, 2 x SATA channel for DVD
LAN Controller	Intel® 82575EB, 2 x 10/100/1000 Mbit/s Ethernet (I/O acceleration), PXE-Boot via LAN from PXE server, iSCSI boot (also diskless) via onboard LAN
Remote Management Controller	Integrated Remote Management Controller (iRMC S2, 32 MB attached memory incl. graphics controller), IPMI 2.0 compatible
Trusted Platform Module (TPM)	Infineon / separate module; TCG V1.2 compliant (option)

SLOTS

PCI-Express 2.0 x4 (mech. x8)	5 x full height from 4 PCIe slots each two wired x4 slots can be combined to one wired x8 slot one PCIe-2 slot is occupied with one of two possible modular RAID controllers
PCI-Express 2.0 x8	2 x full height
Slot Notes	slot 5 and 7 are notched at the right side and thus also usable for x16 cards (operating x8, slot 5 only if neighbor slot is empty)

DRIVE BAYS

Hard disk bay configuration	6x 3.5-inch, for SAS / SATA or 12x 2.5-inch for SAS/SATA optional
Accessible drive bays	3 x 5.25/1.6-inch
Notes accessible drives	All possible options described in relevant system configurator.
Optional hard disk bays	2 x 3.5-inch hot-plug SAS/SATA or 8x 2.5-inch hot-plug SAS in HDD box (occupies 2x 5.25-inch bays)

OPERATING PANEL

Operating buttons	On/off switch NMI button Reset button
Status LEDs	System status (amber / yellow) Identification (blue) Hard disks access (green) Power (amber / green) At system rear side: System status (amber / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow)
Service display	Optional: ServerView Local Service Panel (LSP) ServerView Local Service Display (LSD)

BIOS

BIOS features	ROM based setup utility Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Windows and Linux versions Local and remote update via ServerView Update Manager SMBIOS V2.4 Remote PXE boot support Remote iSCSI boot support
----------------------	--

SUPPORTED OPERATING SYSTEMS

Supported operating systems	Microsoft® Windows Server® 2008 Microsoft® Windows Server® 2003 R2 Novell SUSE Linux Enterprise Server Red Hat Enterprise Linux Note: Support of other Linux derivatives on demand VMware Infrastructure VMware vSphere 4.0
------------------------------------	---

Operating system release link	http://ts.fujitsu.com/software http://docs.ts.fujitsu.com/dl.aspx?id=a9e600b9-e4cb-4f48-aa41-632f69058421
--------------------------------------	--

SERVER MANAGEMENT

Standard	PDA Prefailure Detection and Analysis ASR&R Automatic Server Recovery and Restart ServerView Suite: SV Installation Manager SV Operation Manager SV RAID Manager SV Update Management SV Power Management SV Agents Online update packages for BIOS, firmware drivers and ServerView Agents ServerView Integration solutions for Microsoft SMS, MOM, SCOM, SCCM and Altiris Deployment Solution ServerView Deployment Manager (fully functional 30-day trial version) ServerView Integration solutions for Microsoft SMS, MOM, SCOM, SCCM and Altiris Deployment Solution ServerView Deployment Manager (fully functional 30-day trial version) ServerView Remote Management (iRMC)
Option	ServerView Integration for Tivoli TEC®, Tivoli NetView, HP NNM and HP Operations Manager iRMC S2 Advanced Pack
Server Management notes	Regarding Operating System dependencies and product details for ServerView Suite Software Products see dedicated Product Data sheets.

DIMENSIONS / WEIGHT

Rack (W x D x H)	482.6 mm (Bezel) / 444 mm (Body) x x 176
Mounting Depth Rack	700 mm
Height Unit Rack	4 U
Weight	up to 40 kg
Weight notes	Actual weight may vary depending on configuration
Rack integration kit	Rack integration kit as option

DIMENSIONS / WEIGHT (BASE UNIT SPECIFIC)

Floor-stand (W x D x H)	286 x 745 x 466 mm	286 x 745 x 466 mm
Rack (W x D x H)		483 x 748 x 177 mm
Mounting Depth Rack		710 mm

ENVIRONMENTAL

Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	42dB/42dB
Sound power (LWA; 1B = 10dB)	6.0B/6.0B
Operating ambient temperature	10 - 35°C
Operating relative humidity	10 - 85 % (non condensing)

ELECTRICAL VALUES

Power supply configuration	1x 800 W hot-plug power supply plus three 120mm standard fans or 2x 800W hot-plug power supply plus three hot-plug and redundant double fans
Max. output of single power supply	800 W
Rated voltage range	100 - 240 V
Rated frequency range	47 - 63 Hz
Rated current max.	100 V - 240 V / 9,0 A – 5,0 A
Rated current in basic configuration	100 V - 240 V / 4,4 A - 1,5 A
Active power max. (per system unit)	560 W
Apparent power max. (per system unit)	570 VA
Heat emission	2016.0 kJ/h (1910.8 BTU/h)

COMPLIANCE

Germany	TÜV GS
Europe	CE Class A *
USA/Canada	CSAc/us FCC Class A
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment)
Japan	VCCI Class A + JIS 61000-3-2
Australia/New Zealand	C-Tick
Taiwan	CNS 13438 class A
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

COMPONENTS

HARD DISK DRIVES	SSD SATA, 3 Gb/s, 64 GB, SLC, hot-plug, 2.5-inch, enterprise
	SSD SATA, 3 Gb/s, 32 GB, SLC, hot-plug, 2.5-inch, enterprise
	HDD SATA, 3 Gb/s, 750 GB, 7200 rpm, hot-plug, 3.5-inch, business critical
	HDD SATA, 3 Gb/s, 500 GB, 7200 rpm, hot-plug, 3.5-inch, business critical
	HDD SATA, 3 Gb/s, 500 GB, 7200 rpm, hot-plug, 2.5-inch, business critical
	HDD SATA, 3 Gb/s, 320 GB, 5400 rpm, hot-plug, 2.5-inch, economic
	HDD SATA, 3 Gb/s, 250 GB, 7200 rpm, hot-plug, 3.5-inch, business critical
	HDD SATA, 3 Gb/s, 160 GB, 7200 rpm, hot-plug, 3.5-inch, economic
	HDD SATA, 3 Gb/s, 160 GB, 7200 rpm, hot-plug, 2.5-inch, business critical
	HDD SATA, 3 Gb/s, 160 GB, 5400 rpm, hot-plug, 2.5-inch, economic
	HDD SATA, 3 Gb/s, 2 TB, 7200 rpm, hot-plug, 3.5-inch, business critical
	HDD SATA, 3 Gb/s, 1 TB, 7200 rpm, hot-plug, 3.5-inch, business critical
	HDD SAS, 6 Gb/s, 600 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
	HDD SAS, 6 Gb/s, 450 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
	HDD SAS, 6 Gb/s, 300 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise
	HDD SAS, 6 Gb/s, 300 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 146 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 146 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 6 Gb/s, 73 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise
	HDD SAS, 3 Gb/s, 146 GB, 15000 rpm, hot-plug, 3.5-inch, enterprise

Hard disk notes	Mix of 3.5-inch SAS and SATA HDD is possible but requires separate RAID sets One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software
TAPE DRIVES	DDS Gen5, 36 GB , 3 MB/s, half height, USB 2.0 DDS Gen6, 80 GB , 6 MB/s, half height, USB 2.0 LTO2HH Ultrium, 200 GB , 24 MB/s, half height, SAS 3Gb/s LTO3HH Ultrium, 400 GB , 60 MB/s, half height, SAS 3Gb/s LTO4HH Ultrium, 800 GB , 120 MB/s, half height, SAS 3Gb/s RDX Drive, 80 GB, 160 GB, 320 GB, 500 GB , 25 MB/s, half height, USB 2.0
OPTICAL DRIVES	Blu-ray Disc™ Combo Drive, (2x BD-ROM; 8x DVD; 24x CD), slimline, SATA I Blu-ray Disc™ Combo Drive, (6x BD-ROM; 16x DVD; 40x CD), half height, SATA I DVD-ROM, (16xDVD; 48xCD), half height, SATA I DVD Super Multi, (16xDVD, 8xDVD+RW 6xDVD-RW, 12xDVD-RAM; 48xCD, 32xCD-RW), half height, SATA I DVD Super Multi, (8xDVD/DVD+RW, 6xDVD-RW, 5xDVD-RAM; 24xCD/CD-R, 16xCD-RW), slimline, SATA I
SCSI / SAS CONTROLLER	SCSI Ctrl 320 MB 1ch int/ext PCIe x1 SAS Ctrl 3 Gb 4 ports int. / 4 ports ext. PCIe x4
RAID CONTROLLER	RAID 5/6 Ctrl, SAS 6 Gb, LSI , 8 ports ext. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, optional BBU (based on LSI SAS2108) Integrated RAID 5/6 Ctrl, SAS 6 Gb, Fujitsu , 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, optional BBU (based on LSI SAS2108) Integrated RAID 0/1 Ctrl, SAS/SATA 6 Gb, Fujitsu , 8 ports int. RAID level: 0, 1, 10, no BBU support (based on LSI SAS2008) Integrated RAID 0/1 Ctrl, SAS/SATA 3 Gb, 4 ports int. RAID level: 0, 1, 1E, no BBU support , for internal SAS tapes (based on LSI 1064e)
FIBRE CHANNEL CONTROLLER	Fibre Channel Ctrl 1 x 4 Gb Emulex LPe1150 MMF LC Fibre Channel Ctrl 2 x 4 Gb Emulex LPe11002 MMF LC Fibre Channel Ctrl 1 x 4 Gb Qlogic QLE2460 MMF LC Fibre Channel Ctrl 2 x 4 Gb Qlogic QLE2462 MMF LC Fibre Channel Ctrl 2 x 8 Gb Emulex LPe12002 MMF LC Fibre Channel Ctrl 1 x 8 Gb Emulex LPe1250 MMF LC
LAN CONTROLLER	Converged Network Adapter 2 x 10 Gb Emulex OCe10102 Ethernet Ctrl 1 x 1 Gb Intel® Gigabit CT Desktop Adapter Ethernet Ctrl 1 x 1 Gb Intel® PRO/1000 PF Server Adapter Ethernet Ctrl 1 x 1 Gb Intel® PRO/1000 PT Server Adapter Ethernet Ctrl 2 x 10 Gb Intel® 10 Gigabit XF SR Dual Port Server Adapter Ethernet Ctrl 2 x 10 Gb Intel® Ethernet Server Adapter X520-DA2 Ethernet Ctrl 2 x 1 Gb Intel® PRO/1000 PT Dual Port Server Adapter Ethernet Ctrl 4 x 1 Gb Intel® PRO/1000 PT Quad Port Server Adapter
RACK INFRASTRUCTURE	Cable Arm 2U for 3rd party racks Cable Management for 19-inch DataCenter / PRIMECENTER Racks Rackmount kit full extraction (760mm), tool less mounting
WARRANTY	
Standard Warranty	3 years
Service level	On-site Service (depending on country)
MAINTENANCE AND SUPPORT SERVICES - THE PERFECT EXTENSION	
Recommended Service	7x24, Onsite Response Time: 4h - For locations outside of EMEA please contact your local Fujitsu partner.
Spare Parts availability	5 years
Service Weblink	http://ts.fujitsu.com/Supportservice

FUJITSU PLATFORM SOLUTIONS

In addition to Fujitsu PRIMERGY TX300 S6, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

MORE INFORMATION

Learn more about Fujitsu PRIMERGY TX300 S6, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. <http://ts.fujitsu.com/Primergy>

FUJITSU GREEN POLICY INNOVATION

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment/>



COPYRIGHTS

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html

Copyright © Fujitsu Technology Solutions

DISCLAIMER

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

CONTACT

FUJITSU LIMITED
Mies-van-der-Rohe-Straße 8
80807 München
Germany
Website: www.ts.fujitsu.com
2010-05-27 CE-EN